

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

UNI PRIMER WHITE

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

wood surfaces, indoors

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

WOCA Denmark A/S

Tvæervej 6

6640 Lunderskov

Denmark

Tel: +45 99585600

Fax: +45 99585636

Contact person

LFH

E-mail

info@ttwoodcare.com

SDS date

2017-05-11

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

2.2. Label elements

Hazard pictogram(s)

-

Signal word

-

Hazard statement(s)

-

Safety statement(s)

General -

Prevention -

Response -

Storage -

Disposal -

Identity of the substances primarily responsible for the major health hazards

-

2.3. Other hazards

-

Additional labelling

Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. (EUH208). Safety data sheet available on request. (EUH210)

Additional warnings

-

VOC

VOC-MAX: 110 g/l, MAXIMUM VOC CONTENT (A/i (WB)): 140 g/l.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

2-butoxyethanol

Does not contain any substances required to report

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

S = Organic solvent L = European occupational exposure limit.

Other information

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Nothing special

4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Some metal oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

No specific requirements.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

Store frost-free.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

2-butoxyethanol

Long-term exposure limit (8-hour TWA reference period): 25 ppm | - mg/m³

Short-term exposure limit (15-minute reference period): 50 ppm | - mg/m³

Comments: Sk BMGV (Bmgv = Biological Monitoring Guidance Value. Sk = Can be absorbed through skin.)

DNEL / PNEC

DNEL (2-butoxyethanol): 89 mg/kg/d

Exposure: Dermal

Duration of Exposure: Short term – Systemic effects - Workers

Remarks: brenntag

DNEL (2-butoxyethanol): 663 mg/m³, 135ppm

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (2-butoxyethanol): 246 mg/m³, 50ppm

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (2-butoxyethanol): 75 mg/kg/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-butoxyethanol): 98mg/m³, 20ppm

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

According to EC-Regulation 2015/830

DNEL (2-butoxyethanol): 44,5 mg/kg/d
 Exposure: Dermal
 Duration of Exposure: Short term – Systemic effects - General population
 DNEL (2-butoxyethanol): 426 mg/m³
 Exposure: Inhalation
 Duration of Exposure: Short term – Systemic effects - General population
 DNEL (2-butoxyethanol): 13,4mg/kg/d
 Exposure: Oral
 Duration of Exposure: Short term – Systemic effects - General population
 DNEL (2-butoxyethanol): 123mg/m³
 Exposure: Inhalation
 Duration of Exposure: Short term – Local effects - General population
 DNEL (2-butoxyethanol): 38mg/kg/d
 Exposure: Dermal
 Duration of Exposure: Long term – Systemic effects - General population
 DNEL (2-butoxyethanol): 49mg/m³
 Exposure: Inhalation
 Duration of Exposure: Long term – Systemic effects - General population
 DNEL (2-butoxyethanol): 3,2 mg/kg/d
 Exposure: Oral
 Duration of Exposure: Long term – Local effects - General population
 PNEC (2-butoxyethanol): 8,8mg/l
 Exposure: Water
 Remarks: Brenntag
 PNEC (2-butoxyethanol): 0,88mg/l
 Exposure: Marine water
 PNEC (2-butoxyethanol): 463 mg/l
 Exposure: Sewage Treatment Plant
 PNEC (2-butoxyethanol): 34,6 mg/kg
 Exposure: Freshwater sediment
 PNEC (2-butoxyethanol): 3,46 mg/kg
 Exposure: Marine water sediment
 PNEC (2-butoxyethanol): 2,8 mg/kg
 Exposure: Soil

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, eating and drinking are not allowed in the work premises

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements.

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

Hand protection

Recommended: Nitrile rubber. See the manufacturer's instructions.

Eye protection

Wear face shield alternatively safety glasses with side shields.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Form	Liquid
Colour	No data available.
Odour	No data available.
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	No data available.

Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

Data on fire and explosion hazards

Flash point (°C)	No data available.
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

Solubility

Solubility in water	Soluble
n-octanol/water coefficient	No data available.

9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Substance	Species	Test	Route of exposure	Result
2-butoxyethanol	Rat	LD50	Oral	1746 mg/kg
2-butoxyethanol	Rat	LD50	Dermal	>2000mg/kg

Skin corrosion/irritation

No data available.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Nothing special

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Duration	Result
2-butoxyethanol	Fish	LC50	96h	1474mg/l
2-butoxyethanol	Daphnia	EC50	48h	1550mg/l
2-butoxyethanol	Algae	EC50	72h	1840mg/l
2-butoxyethanol	Crustacean	EC0	16h	700mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
No data available.			

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

Nothing special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Waste

EWC code

-

Specific labelling

-

Contaminated packing

No specific requirements.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

14.1. UN number	-
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	-
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

IMDG

UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-
EmS	-
MP**	-
Hazardous constituent	-

IATA/ICAO

UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

-

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H302 - Harmful if swallowed.

H312 - Harmful in contact with skin.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

The full text of identified uses as mentioned in section 1

-

Additional label elements

-

Other

In accordance with Article 31 of REACH a safety data sheet is not required for this product. This safety data sheet has been created on a voluntary basis. In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of physical hazards has been based on experimental data.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

LFH

**Date of last essential change
(First cipher in SDS version)**

-

**Date of last minor change
(Last cipher in SDS version)**

-