



1 PREPARE 2 TREAT 3 MAINTAIN

# EXTERIOR WOOD SHIELD



### For outdoor wood

For protection of untreated outdoor wooden surfaces, such as garden furniture and patios.



### High resistance

Increases the resistance of wood to wind and weather.



### Natural patina

Protects the untreated surface and retains the patina of the wood. Extends the lifetime of the wood.

### APPLICATION AREA

Exterior Wood Shield is used for protection of all types of outdoor, untreated wood surfaces, composites and stone. Ideal for wooden garden furniture and patios with grey patina.

### RESULT

Exterior Wood Shield produces a water- and grime-resistant surface, while retaining the patina of the wood, as it does not add colour to it. It also extends the lifetime of the wood.

### Product information

Coverage: 20-30 m<sup>2</sup>/L  
Packaging: 1 L and 2.5 L  
Available in Transparent



# HOW TO...

## ...MAINTAIN UNTREATED WOOD OUTDOORS

### *Tools*

The wood shield is preferably applied with a spraygun or brush, or by dipping the wood

### *Preparation*

The surface must be completely dry and free of dust, dirt and algae. For optimum protection, we recommend light sanding of the surface afterwards, so the wood is completely smooth and pleasant to walk on.

### *Risk of self-ignition!*

Any cloths that have been soaked in oil should be stored/ disposed of in sealed containers or incinerated due to risk of self-ignition.

### *Please note*

Surfaces treated with Exterior Wood Shield cannot be painted or oiled and should therefore be sanded down and cleaned with WOCA Exterior Deep Cleaner before treating the wood with WOCA Exterior Wood Oil.

### *Maintenance and cleaning*

It is a good idea to retreat the surface 1-2 times a year to achieve optimum protection.



## INSTRUCTIONS

- 1 Shake the container well.
- 2 Apply Exterior Wood Shield using a spraygun, brush or by dipping the wood. It is important that the product is applied thoroughly and evenly.

For application using a spraygun, keel the spray nozzle approx. 10-15 cm from the surface.

- 3 Leave the wood to dry.

Exterior Wood Shield does not give full protection until 2-4 days have passed.