



① PREPARE ② TREAT ③ MAINTAIN

MASTER FILLER CLASSIC

PRODUCT DESCRIPTION

Master Filler Classic is a fast-drying solvent-based gap filler for joints and gaps in wooden floors, such as Nordic and herringbone pattern parquet. It is easy to work with and shortens the work process due to its fast drying time.

APPLICATION AREA

For filling new, untreated, newly sanded and previously treated wood. Ideal for all species of wood.



Quick-drying

Drying time before sanding: 30 minutes at 20°C. For larger joints, the filler should be left to dry until the following day.



Easy to sand

Thick consistency. Solvent-based. Easy to sand once it has cured.



Even, uniform finish

Once the filler is cured and sanded, the smooth and uniform surface is ready for further treatment.

Product information

Coverage: 15-20 m²/L

Packaging: 5 L



WORK DESCRIPTION

Preparation

The surface must be completely clean, dry and free of dust, wax, grease, polish, etc. Remove grime and irregularities using a sanding machine. Use grit 60-80 sandpaper for the final sanding before application of Master Filler Classic.

Mixing ratio

Approx. 20% sanding residue - depending on the colour of the wood and the depth/width of the join.

Note

Optimal join width is 3-4 mm.



APPLY



SAND



APPLY LACQUER

TREATMENT

- 1 Shake the container well before use.
- 2 Mix the Master Filler Classic and the sanding residue into a nice and soft paste. The structure of the filler can be adjusted using the fine or coarse sanding residue. We recommend the use of sanding residue from grit 100.
- 3 Distribute the filler evenly, using a stainless steel applicator. Repeat if necessary.
- 4 Sand the surface with grit 80-120 sandpaper once the surface is dry.
- 5 The surface can then be lacquered using one of WOCA's lacquers, following the product instructions.