



1 PREPARE 2 TREAT 3 MAINTAIN

DIAMOND OIL

PRODUCT DESCRIPTION

Diamond Oil is used for oil finishing of wooden floors with floor machine. The oil ensures an extremely hard-wearing, dirt- and water-repellent surface. Diamond Oil is ideal for basic finishing of any unfinished, new and newly sanded interior woodwork. Content of

solvent is less than 1 %. Floor machine is recommended for the polishing of bigger areas.

APPLICATION AREA

For oil finishing of unfinished, new and newly sanded wood.

Product information

Coverage: 20-25 m²/L

Packaging: 1 L + 2.5 L

Colours: 9 colours*

* Natural, White and Extra White = 1 L



High resistance

Robust surface with high resistance to scratches, spills and stains. Extremely high solids content.



Natural appearance

Penetrates deep into the wood. Emphasizes the natural grain for a more attractive look. For all types of wood.



Easy application

The oil is smooth and pleasant to work with. Can be applied both manually and by machine. Fast-drying.



Indoor climate labelled

Ensures a good working environment during application. Does not harm indoor air quality. Water-based.





WORK DESCRIPTION

Preparation

The unfinished woodwork should be freshly sanded with grit 100-120. The floor must be completely dry and free from dirt and grease before the oil application. Recommended wood-moisture max. 12 %. Product, room and floor temperature should be between 15°C–30°C. Ensure good ventilation at all times during the application and drying time.

The floor can be cleaned with WOCA Intensive Wood Cleaner mixed with water 1:40 if necessary. Leave floor to dry fully before oil application.

Risk of self-ignition

Due to the risk of self-ignition it is important that oil wetted cloths are soaked and disposed of in a tightly closed and water filled container after use.

Note

Do not expose the floor to water during hardening time – approx. 3 days, depending on air-temperature and moisture. After the hardening time, the floor should be cleaned with Natural Soap or Oil Refreshing Soap, which leaves a protecting layer on the surface.

Maintenance and cleaning


Weekly cleaning: Natural Soap

Monthly care: Oil Refreshing Soap

Re-oiling: Maintenance Oil or Maintenance Gel




CLEANING



APPLICATION



POLISHING



WIPING OFF

TREATMENT

- 1 Shake oil container well before use. Containers with different batch numbers should be mixed before use to avoid colour differences. Apply the oil with a short-haired paint roller in an even coat onto approx. 5-10 m² of floor.
- 2 Leave the oil to be absorbed for 5-10 minutes. If dry spots appear, apply more oil.
- 3 The area is now polished with beige polishing pad under doo-dlebug or with floor machine until surface appears saturated.
- 4 Polish the floor after using cotton cloth under floor pad to remove any possible excess oil. Continue stepwise till the whole floor has been polished. The floor should not appear wet and there should not be any excess oil left on the surface after polishing.
- 5 After 6-8 hours, the floor should be dry-buffed with Extra White polishing pad. If a silk-mat surface is required, the finished floor may be buffed with 100 ml. of Diamond Oil to 10 m² of floor. This is done between 6-18 hours after first application. The oil must be polished carefully into the floor. Remove any excess oil from the surface.
- 6 After 24 hours the floor can be used with caution.